









HandySCAN3D > ™

WHEN ACCURACY MEETS VERSATILITY AND PORTABILITY

The HandySCAN 3D™ line-up is the industry standard in portable metrology-grade 3D scanners and a proven and trusted patented technology. Optimized to meet the needs of design, manufacturing and metrology professionals, the BLACK Series provides the most effective and reliable way to acquire accurate 3D measurements of physical objects anywhere.

Portable, accurate and simple to use, the HandySCAN 3D | BLACK Series features unmatched speed that captures high-quality measurements. Since it performs regardless of environment changes or part movement, it represents the ideal tool for quality assurance and product development applications.



ACCURACY OF 0.025 mm



SCAN-TO-MESH IN SECONDS



CERTIFIED ISO 17025



WORLDWIDE SUPPORT



LARGE SCANNING AREA



PATENTED TECHNOLOGY





- High-performance optics
 Optimal scan quality
- 2 Extra single line
 Easy capture of hard-to-reach
 areas
- 3 Blue laser technology High resolution capability
- Stand-off distance color indicator Maximizes scanning performance
- Multifunction buttons
 Quick access to frequently used
 software functionalities
- Highly ergonomic and sleek design Provides outstanding user experience



The HandySCAN 3D | BLACK Series delivers accurate, high-resolution and repeatable results, regardless of the measurement setup quality and no matter the user experience. Featuring dynamic referencing, both the scanner and part can move during measurement and still provide an accurate and high-quality scan.

Accuracy

0.025 mm

Volumetric accuracy

0.020 + 0.040 mm/m

Reliable acceptance test

Based on VDI/VDE 2634 part 3 standard ISO 17025 accredited laboratory

High resolution for fine details

This handheld 3D scanner is a stand-alone device that does not require a tripod nor any external tracking device to operate. Fitting in a small suitcase, it can be brought anywhere and used in any environmental conditions without affecting its performance.

Lightweight

0.94 kg

Dynamic referencing

Both the object and scanner can be moved freely while scanning

Fits into a suitcase

Take it anywhere you need

With its user-friendly interface and ergonomic design, this 3D measurement solution has a short learning curve. Highly versatile, it can be used to scan various object sizes and surface types in real time—all with the same device.

Plug and play

Simple user interface and real-time mesh visualization

Single device fits all needs

Masters complex and difficult surfaces

The HandySCAN 3D | BLACK Series scanner features multiple laser crosses and an automatic mesh generation, enabling a faster workflow from the set-up to the scan and then to the file!

Instant mesh

Ready-to-use files

High measurement rate

Up to 1,300,000 measurements/s

11 laser crosses scanning area

Quick set-up

Up and running in less than 2 minutes

TECHNICAL SPECIFICATIONS

Innovating technology that provides accuracy, simplicity, portability as well as real speed to your metrology-grade applications.

HandySCAN BLACK™

HandySCAN BLACK™|Elite

ACCURACY ⁽¹⁾	0.035 mm	0.025 mm
VOLUMETRIC ACCURACY ⁽²⁾ (based on part size)	0.020 mm + 0.060 mm/m	0.020 mm + 0.040 mm/m
VOLUMETRIC ACCURACY WITH MaxSHOT Next™IElite (3)	0.020 mm + 0.015 mm/m	
MEASUREMENT RESOLUTION	0.025 mm	
MESH RESOLUTION	0.100 mm	
MEASUREMENT RATE	800,000 measurements/s	1,300,000 measurements/s
LIGHT SOURCE	7 blue laser crosses	11 blue laser crosses (+ 1 extra line)
LASER CLASS	2M (eye safe)	
SCANNING AREA	310 x 350 mm	
STAND-OFF DISTANCE	300 mm	
DEPTH OF FIELD	250 mm	
PART SIZE RANGE (recommended)	0.05-4 m	
SOFTWARE	VXelements	
OUTPUT FORMATS	.dae, .fbx, .ma, .obj, .ply, .stl, .txt, .wrl, .x3d, .x3dz, .zpr, .3mf	
COMPATIBLE SOFTWARE (4)	3D Systems (Geomagic® Solutions), InnovMetric Software (PolyWorks), Metrologic Group (Metrolog X4), New River Kinematics (Spatial Analyzer), Verisurf, Dassault Systèmes (CATIA V5, SOLIDWORKS), PTC (Creo), Siemens (NX, Solid Edge), Autodesk (Inventor, PowerINSPECT)	
WEIGHT	0.94 kg	
DIMENSIONS (LxWxH)	79 x 142 x 288 mm	
CONNECTION STANDARD	1 X USB 3.0	
OPERATING TEMPERATURE RANGE	5-40°C	
OPERATING HUMIDITY RANGE (non-condensing)	10-90%	
CERTIFICATIONS	EC Compliance (Electromagnetic Compatibility Directive, Low Voltage Directive), compatible with rechargeable batteries (when applicable), IP50, WEEE	
PATENTS	CA 2,600,926, CN 200680014069.3, US 7,912,673, CA 2,656,163, EP (FR, UK, DE) 1,877,726, AU 2006222458, US 8,032,327, JP 4,871,352, US 8,140,295, EP (FR, UK, DE) 2,278,271, EP (FR, UK, DE) 2,230,482, IN 266,573, US 7,487,063, CA 2,529,044, EP (FR, UK, DE) 3,102,908, US 15/114,563, CN 201580007340X	

- (1) HandySCAN BLACK and HandySCAN BLACK|Elite (ISO 17025 accredited): Based on VDI/VDE 2634 part 3 standard. Probing error performance is assessed with diameter measurements on traceable sphere artefacts.
- (2) HandySCAN BLACK and HandySCAN BLACK|Elite (ISO 17025 accredited): Based on VDI/VDE 2634 part 3 standard. Sphere-spacing error is assessed with traceable length artefacts by measuring these at different locations and orientations within the working volume.
- (3) The volumetric accuracy of the system when using a MaxSHOT 3D cannot be superior to the default accuracy for a given model.
- (4) Also compatible with all major metrology, CAD, and computer graphic software through mesh and point cloud import.



AMETEK GmbH

Division Creaform DeutschlandMeisenweg 37
D - 70771 Leinfelden-Echterdingen
T.: +49 711 1856 8030 | F.: +49 711 1856 8099

AMETEK®

Authorized Distributor





HandySCAN 3D, HandySCAN BLACK, HandySCAN BLACK| Elite, MaxSHOT 3D, MaxSHOT Next| Elite, VXelements, and their respective logo are trademarks of Creaform Inc. © Creaform inc. 2021. All rights reserved. V3